

**PONDICHERY UNIVERSITY  
ENGINEERING WING**

**Name of Work: Maintenance of E-10 and D-10 Quarters to arrest the Leakage**

**SCHEDULE OF WORK**

<b>S.No</b>	<b>Description</b>	<b>Qty</b>	<b>Rate</b>	<b>Unit</b>	<b>Amount</b>
1	<b>Code no:15.23.1</b>				
	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50m lead - For thickness of tiles above 10mm and upto 25mm.	155.00		Sqm	
2	<b>Code no:12.20</b>				
	Providing and laying pressed clay tiles (as per approved pattern 18mm nominal thickness and of approved size) on roofs jointed with cement mortar 1:4 (1 cement : 4 coarse sand) mixed with 2% intergral water proofing compound laid over a bed of 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) and finished neat complete.	155.00		Sqm	
3	<b>Code no:15.56</b>				
	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50m lead.	25.00		Sqm	
4	<b>Code no:13.5.1</b>				
	15mm cement plaster on rough side of single or half brick wall of mix - 1:4 (1 cement : 4 coarse sand)	25.00		Sqm	
5	<b>Code no:13.47.1</b>				
	Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade - New work (Two or more coats applied @ 1.43 ltr / 10 sqm over and including base coat of water proofing cement paint applied @ 2.20 kg/10 sqm).	25.00		Sqm	
6	<b>Code no:14.67.2</b>				
	Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade - Old work (one or more coats applied @ 0.83 ltr/10 sqm)	580.00		Sqm	

<b>7</b>	<b>Code no:14.45.1</b>				
	Distemping with oil bound washable distemper of approved brand and manufacture to give an even shade - Old work (one or more coats).	290.00		Sqm	
<b>8</b>	<b>Code no:14.54.1</b>				
	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade - One or more coats on old work.	230.00		Sqm	
<b>9</b>	<b>Code no:14.42.2</b>				
	White washing with lime to give an even shade - Old work (one or more coats).	270.00		Sqm	
<b>10</b>	<b>Code no:9.16.1.1P</b>				
	Providing and fixing 25 mm thick shutters for cup board etc - Panelled or panelled & glazed shutters - Padak wood including ISI marked anodised aluminium butt hinges with necessary screws	2.30		Sqm	
<b>11</b>	<b>Code no:9.97.2</b>				
	Providing and fixing aluminium tower bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour or shade with necessary screws etc.complete : 250x10mm	4.00		Each	
<b>12</b>	<b>Code no:9.100.1</b>				
	Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour or shade with necessary screws etc.complete : 125mm	4.00		Each	
<b>13</b>	<b>Code no:13.50.1</b>				
	Applying priming coat - with ready mixed pink or grey primer of approved brand and manufacture on wood work (hard and soft wood).	6.00		Sqm	
<b>14</b>	<b>Code no:13.61.1</b>				
	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade - Two or more coats on new work.	11.50		Sqm	

<b>15</b>	<b>Code no:10.26.3</b>				
	Providing and fixing hand rail of approved size by welding etc. to steel ladder railing, balcony railing and staircase railing including applying a priming coat of approved steel primer. G.I. pipes.	40.00		Sqm	
<b>16</b>	<b>Code no:12.20L</b>				
	Lime concrete terracing on roofs of required thickness laid to fall with 25mm nominal size brick aggregate and 50% lime mortar 1:2 (1 lime putty : 2 surkhi) rammed and finished with gur and belgiri treatment complete including rounding of junctions with parapet wall complete	1.50		Cum	
<b>17</b>	<b>Code no:MR</b>				
	Supply and Apply of Dr.Fixit Heavy duty, reinforced acrylic coating, new coat for open terrace.(Three or more coats 1mm thick for finished layer etc., complete as directed	86.00		Sqm	
<b>18</b>	<b>Code no:MR</b>				
	Clean the surface, supply and apply of quick setting chemicals and Polysulphide sealent in the floor trap area, so as to complete seal the water leakage in the RCC slab.	1.00		Job	
				<b>Total</b>	

I hereby abide the rules and regulations stipulated in the CPWD form no. 6 & 8.

**Contractor**

**Assistant Engineer**